CLAIMS:

Sub a'

1   1.   A method of updating a communications key maintained in a unit for
2   communicating with a communications system, said method comprising:
3   generating a new communications key using a secret value stored in said unit;
4   generating an update key using said secret value stored in said unit;
5   performing an authentication using said update key; and
6   updating said communications key with said new communications key after
7   said authentication.

1   2.   The method of claim 1 comprising:
2   receiving an update sequence;
3   generating said new communications key using a secret value stored in said
4   unit and said sequence;
5   generating a signature value using said update key; and
6   comparing said signature value with a signature value received from said
7   communications system which was generated using said update key to perform said
8   authentication.

1   3.   The method of claim 2 further comprises:
2   generating a challenge sequence;
3   sending said challenge sequence to said communications system;
4   generating said signature value using said challenge sequence and said update
5   key;
6   receiving a signature string generated by said communications system using
7   said challenge sequence and said update key; and
8   comparing said signature value with said signature value generated by said
9   communications system.

1   4.   The method of claim 3 comprises:

2   generating a second signature value using said update sequence and said

3   update key; and

4   sending said second signature value to said communications system for

5   comparison with a second signature value generated by said communications system

6   using said sequence and said update key generated at said communications system.

1   5.   The method of claim 3 wherein said generating said signature value

2   includes:

3   developing a signature string comprising at least portions of said update

4   sequence, said challenge sequence and said update key; and

5   generating said signature value from at least said signature string.

1   6.   The method of claim 4 wherein said generating said signature value

2   includes:

3   developing a second signature string comprising at least portions of said

4   update sequence, said challenge sequence and said update key; and

5   generating said second signature value from at least said second signature

6   string.

1   7.   A method of updating a communications key maintained in a unit and

2   in a communications system, said method comprising:

3   sending to said unit an update sequence for said unit to generate a new

4   communications key using a secret value in said unit;

5   sending to said unit a signature value for said unit to compare said signature

6   value generated at said communications system using an update key derived from a

7   secret value stored in said communications system associated with said unit; and

8   receiving an update confirmation after which said communications key is

9   updated with said authentication.

1   8.   The method of claim 7 comprising:

2   generating said signature value.

1   9.   The method of claim 8 wherein said generating a signature value

2   including:

3   receiving a challenge sequence from said unit; and

4   generating said signature value using said challenge sequence and said update

5   key.

1   10.   The method of claim 9 including:

2   generating a second signature value using said update sequence and said

3   update key; and

4   receiving a second signature value generated at said unit using said update

5   sequence and said update key at said unit;

6   comparing with said second signature value with said second signature value

7   generated by said unit.

1   11.   The method of claim 10 wherein said generating a signature value

2   including:

3   developing a signature string comprising at least portions of said update

4   sequence, said challenge sequence and said update key; and

5   generating said signature value from at least said signature string.

1   12.   The method of claim 10 wherein said generating a second signature

2   value including:

3   developing a second signature string comprising at least portions of said

4   update sequence, said challenge sequence and said update key; and

5   generating said second signature value from at least said second signature

6   string.

27

1   13.   A method of updating a communications key maintained in a unit and

2   in a communications system, said method comprising:

3   generating an update sequence; and

4   generating a new communications key using a secret value stored in said

5   communications system and associated with said unit and said update sequence;

6   generating an update key using said secret value and said update sequence;

7   updating said communications key with said new communications key after

8   an authentication is performed with said unit using said update key.

1   14.   The method of claim 13 further comprising:

2   providing said update key to generate a signature value using said update key

3   in said communications system to compare at said unit said signature value with a

4   signature value generated at said unit using an update key generated at said unit using

5   said update sequence and a secret value stored in said unit; and

6   updating said communications key with said new communications key after

7   receiving the results of said comparison of said signature values.

1   15.   A method of updating a communications key maintained in a unit and

2   in a home communications system, said method comprising:

3   receiving an update sequence from said home communications system for said

4   unit to generate a new communications key using a secret value in said unit;

5   receiving an update key from said from said home communications system

6   and generated at said home communications system using a secret value associated

7   with said unit at said home communications system;

8   performing an authentication with said unit using said update sequence; and

9   sending to said home communications system the results of said

10   authentication.